



US009638440B2

(12) **United States Patent**  
**Payne**

(10) **Patent No.:** **US 9,638,440 B2**

(45) **Date of Patent:** **May 2, 2017**

(54) **SOLAR BOILER PANEL ARRANGEMENT**

(56) **References Cited**

(71) Applicant: **ALSTOM Technology Ltd.**, Baden  
(CH)

U.S. PATENT DOCUMENTS

(72) Inventor: **Ronald G. Payne**, West Simsbury, CT  
(US)

4,245,618 A 1/1981 Wiener  
4,974,888 A \* 12/1990 Childers ..... F16B 37/0857  
292/251  
2010/0199978 A1 8/2010 Plotkin et al.  
2010/0199980 A1 8/2010 Ricci et al.

(73) Assignee: **ALSTOM Technology Ltd.**, Baden  
(CH)

FOREIGN PATENT DOCUMENTS

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 1164 days.

CN 2267436 Y 11/1997  
CN 2268228 Y 11/1997  
EP 0106687 A2 4/1984  
EP 0106688 A2 4/1984

\* cited by examiner

(21) Appl. No.: **13/675,143**

(22) Filed: **Nov. 13, 2012**

*Primary Examiner* — Avinash Savani

*Assistant Examiner* — Aaron Heyamoto

(74) *Attorney, Agent, or Firm* — Dority & Manning, P.A.

(65) **Prior Publication Data**

US 2014/0130792 A1 May 15, 2014

(57) **ABSTRACT**

(51) **Int. Cl.**

**F24J 2/46** (2006.01)

**F22B 1/00** (2006.01)

**F24J 2/07** (2006.01)

**F24J 2/52** (2006.01)

**F24J 2/24** (2006.01)

(52) **U.S. Cl.**

CPC ..... **F24J 2/4647** (2013.01); **F22B 1/006**  
(2013.01); **F24J 2/07** (2013.01); **F24J 2/24**  
(2013.01); **F24J 2/4636** (2013.01); **F24J 2/52**  
(2013.01); **Y02E 10/41** (2013.01); **Y02E 10/47**  
(2013.01)

(58) **Field of Classification Search**

CPC ..... **F24J 2/4636**; **F24J 2/4607**

USPC ..... **126/663–655**, **658–662**, **674**

See application file for complete search history.

A solar boiler **300** includes first and second primary receiver panels **500**, **600** spaced apart by a gap **700**. Each panel **500**, **600** include a plurality of primary boiler tubes **510**, **610** for receiving solar flux. The boiler **300** includes at least one secondary receiver arrangement **800** disposed across the gap **700** for receiving solar flux incident thereacross. The arrangement **800** includes at least one secondary boiler tube **810**, and at least one support member **820** supported thereto. The arrangement **800** is configured relative to the primary panels **500**, **600** such that endmost primary boiler tubes **510a**, **610a** are supported over the support member **820** in spaced relation 'S' to the secondary boiler tube **810** for enabling transverse and lateral thermal expansion of the tubes **510**, **610**, **810** without bending out. Further, a panel joining attachment **900** is provided for attaching the panels **500**, **600** and the arrangement **800**.

**9 Claims, 3 Drawing Sheets**

